URBAN STYLE





AZIMUT



COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001=
= ISO 14001=
= OHSAS 18001=





AZIMUT

The AZIMUT range of attachment supplied by TECNOINDUSTRIE MERLO S.p.A. comprises rear loader minicompactors, with unloading by tipping over the bucket, fitted with an articulated single-blade compaction system with a rotary blade and a slide running on straight guideways. The central rear part of the attachment houses the bin pick-up, lifting and emptying system (optional) with a possible load-assist device. The attachment is compliant with Machinery Directive 2006/42/CE and is certified by an independent notified body.

CHARACTERISTICS AND STANDARD EQUIPMENT	AZIMUT 6	AZIMUT 8
Dump body volume (m3)	5.5	8
Total mass on ground (kg)	3500 - 5200	5000 - 8000
Compaction system	Articulated single loader blade	
Compaction cycle	Manual / automatic / synchronised	
Adjustable compaction ratio	From 1:1 to 4:1	
Discharge system	By means of dump body tip-up	
Unloading into larger compactors	•	•
Rear infra-red camera with colour monitor in the cab	•	•
Rear white LED beacon	•	•
Dual rotation bin tip-up device	0	0
Flashing yellow LED beacon	•	•
Bin identification system	0	0
Merlo Mobility satellite management system	0	0
Load weighing device	0	0
Rear platform for operators	0	0
STAINLESS STEEL dump body	-	0
ALUMINIUM dump body	0	-
Hybrid version	-	0

● as standard ○ on request

Compaction cycle with articulated single blade



